

Portable Salamander Heaters

Product features

- Long-life finned tubular heating elements
- Built-In thermostat and safety thermal cutout
- Auto reset overheat protection operation
- Tip-over switch for extra safety
- 10" wheels and handle for easy transport and portability
- Heavy-duty steel frame, Safety guards on both intake and output ends
- Powder coating for all steel parts, and cabinet color is optional
- Our portable salamander heaters are perfect for heating up workshop, factory, garage, construction sites
- All models with CSA, UL, cETL listed.



Average Minutes To Achieve Temp Rise

AREA SIZE:	1000 SQ.FT		1500 SQ.FT		2000 SQ.FT	
	TEMP RISE		TEMP RISE		TEMP RISE	
HEATER	20°F	40°F	20°F	40°F	20°F	40°F
10 KW	70 MIN	140 MIN	105 MIN	210 MIN	-	-
15 KW	47 MIN	94 MIN	71 MIN	142 MIN	94 MIN	188 MIN
30 KW	23 MIN	46 MIN	35 MIN	70 MIN	47 MIN	94 MIN

NOTE: Based on a 15' ceiling height. Lower ceiling height will reduce the time

Technical Specification

Model	KW	BTUs	VOLTS	PH	AMPS	CFM	TEMP Rise.F	Dimension (D*W*H) (cm)	Weight (kg)	Loading Q'ty (20GP/40HQ)
WMPSH10-241	10	34120	240	1	41.7	1500	46	71.1*97.8*55	33.1	81/228
WMPSH15-203	15	51180	208	3	41.7	1500	61	71.1*97.8*55	31.8	81/228
WMPSH15-241	15	51180	240	1	62.5	1500	46	71.1*97.8*55	31.8	81/228
WMPSH15-243	15	51180	240	3	36.1	1500	46	71.1*97.8*55	31.9	81/228
WMPSH15-483	15	51180	480	3	18.1	1500	46	71.1*97.8*55	32.7	81/228
WMPSH30-483	30	102389	480	3	36	1900	65	71.1*97.8*55.8	37.1	81/204



CONTACT WITH US

WINMORE GROUP (CHINA) CO.,LTD//XIAMEN WINMORE TRADE CO.,LTD

Add: 2308, Taidi Haixi Center Building B, Haicang District, Xiamen City, China

W: www.winmorehvac.com E: mathew@winmorehvac.com Tel: 0086-592-6050171

Portable Fan Forced Heaters



Product features

- Moveable up from 350 to 600 CFM airflow
- Built-In adjustable Thermostat offers versatility
- Wheels provide easy portability, wall/ceiling hanger optional
- Auto reset overheat protection operation
- Adjustable louvers allow heating directional control
- Tilt adjustment knob for reduced unit footprint and position adjustability
- Powder coating for all steel parts, and cabinet color is optional
- Our portable fan forced heaters direct and push out reliable heat to keep productivity and comfort on the rise at your workshop, factory, automotive garage, construction sites and any other workstation that desires a well heated interior space. More ideal spaces include shops, maintenance rooms, basements, clean room, stairwells, power stations, mechanical rooms, stock rooms, etc.
- All models with CSA, UL, cETL listed.

Technical Specification

Model	KW	BTUs	VOLTS	PH	AMPS	CFM	PLUG TYPE	Dimension (D*W*H) (cm)	Weight(kg)	Loading Q'ty (20GP/40HQ)
WMPEH50	5	20472	208/240	1	18.2	360	Hardwired	54*42*73.5	12.3	300/800
WMPEH75	7.5	25590	240	1	30	400	Hardwired	54*42*73.5	13	160/408
WMPEH100	10	34120	240	3	41.71	600	Hardwired	61*53*83	22.8	84/225



CONTACT WITH US

WINMORE GROUP (CHINA) CO.,LTD//XIAMEN WINMORE TRADE CO.,LTD

Add: 2308, Taidi Haixi Center Building B, Haicang District, Xiamen City, China

W: www.winmorehvac.com E: mathew@winmorehvac.com Tel: 0086-592-6050171